




Features

- Fully sealed assembly
- Updated and efficient design
- Structural waterproofing
- Mounting adapters available
- Available "Dusk to Dawn" sensor



Applications

- Roadways
- Commercial locations
- Outdoor overhead

Specification

| Power | 100W | 200W | 300W | 400W |
|------------------|--|---------------------------------|---------------------------------|---------------------------------|
| Solar panel | 12.8W DOUBLE SIDED | 15.4W DOUBLE SIDED 315x190mm | 20.3W DOUBLE SIDED 429x190mm | 28.1W DOUBLE SIDED 554x190mm |
| Product size | 330*220*60mm | 390*220*60mm | 550*230*60mm | 680*240*60mm |
| Battery | 3.2V/3600mAH | 3.2V/4800mAH | 3.2V/7200mAH | 3.2V/9600mAH |
| LED chip | 96PCS | 210PCS | 320PCS | 400PCS |
| Luminous | 70m2 | 100m2 1400LM | 150m2 | 200m2 |
| N.W | 0.9KG | 1.05KG | 1.5KG | 2.2KG |
| PCS/CTN | 20 | | 10 | |
| CTN size | 60*35*44cm | 60*42*48cm | 55*33*49cm | 70*33*50cm |
| Material | ABS engineering plastic + Glass | | | |
| Working modes | Remote + light control + motion sensor | | | |
| Charging time | 6-8H | | | |
| Discharging time | 36-60H | | | |
| Warranty | 2 years | | | |